



DYNAHUME™ SW

0-0-1

Guaranteed Analysis

Soluble Potash (K₂O) 1%

Derived from Potassium Hydroxide.

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS

Active Ingredients:

Humic Acid (derived from Leonardite) ..	10.00%
Alkylphenyl-hydroxypolyoxyethylene	1.5%
Polydimethylsiloxane	0.018%
Soluble Seaweed Extract	0.5%
Fertilizer:	1.00%
Other Inert Ingredients	86.982%
Total:	100.00%

Information regarding the contents and levels of metals in this product is available on the internet at www.aapfco.org/metals.html.

Information about the components of this lot of fertilizer may be obtained by writing to Schaeffer Manufacturing Co. at the address on this label, and giving the batch number on this container.

Schaeffer Manufacturing Co.

102 Barton St., St. Louis, MO 63104

Questions or comments: Call 1-800-325-9962

www.schaeffercrops.com

Emergency telephone number:

1-314-865-4105 (24-hr response)

KEEP OUT OF REACH OF CHILDREN

This product is non-hazardous per OSHA Hazard Communication Standard (29 CFR 1910.1200) (GHS).

The Safety Data Sheet (SDS) can be downloaded at: www.schaeffercrops.com.

GENERAL INFORMATION

DynaHume™ SW is a one of a kind humic acid product which may aid in micronutrient uptake. DynaHume™ SW also includes our proprietary non-ionic surfactant. It is not recommended to apply DynaHume™ SW to the foliage of plants.

DIRECTIONS FOR USE

In Furrow: Apply 1-2 quarts of DynaHume™ SW per acre. Mix with water before use. Use a minimum of 7 gallons of total solution.

Irrigation and Broadcast: Apply 1-2 gallons of DynaHume™ SW per acre. Mix with water before use. Use a minimum of 7 gallons of total solution.

COMPATIBILITY

DynaHume™ SW is compatible with most common foliar pesticides and nutrients; however, USER ASSUMES FULL RESPONSIBILITY to ensure compatibility when tank mixing with other products. It is not recommended to use this product with other surfactants or adjuvants.

STORAGE CONDITIONS

Do not store with food, feed or other material to be used or consumed by humans or animals. Store at temperatures between 40°F and 95°F. Store in original containers only. Keep containers tightly closed when not in use. DO NOT FREEZE.

DISPOSAL CONDITIONS

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

CONDITIONS OF SALE AND LIMITATION OF WARRANTY AND LIABILITY

The manufacturer warrants that this product is suited for the labeled uses when applied according to label directions. Because of varying conditions, it is impossible to eliminate all risk when labeled directions are followed. Therefore, the manufacturer makes no other implied or express warranty nor is any manufacturer's agent allowed to do so.

Upon purchase, the buyer assumes all risk associated with the use of this product. In the event of damage resulting from a breach of warranty, the buyer agrees to accept a refund of the purchase price of the product as full discharge of the manufacturer's liability.

NET VOLUME and WEIGHT

■ 55 Gal. (208.1 L) / 478.5 lb. (216.7 kg.)

■ 275 Gal. (1040.9 L) / 2392.5 lb. (1083.5 kg.)

WEIGHT PER GALLON:

8.70 lb. (3.84 kg.) @ 68°F